



FTL12-100 (12V100Ah)

FT (Front Terminal) Series is specially designed for telecom use with 15 years design life in float service. By adopting a new AGM separator and centralised venting system, the battery can be installed in any position while maintaining high reliability. The dimensions of the FT series is designed for 19" and 23" cabinet installation. It is suitable for UPS/EPS applications.




Specification


Cells Per Unit	6
Voltage Per Unit	12
Capacity	100Ah@10hr-rate to 1.80V per cell @25°C
Weight	Approx.33.0Kg (Tolerance ±2%)
Max. Discharge Current	1000 A (5 sec)
Internal Resistance	Approx.4.8 mΩ
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Float charging Voltage	13.6 to 13.8 VDC/unit Average at 25°C
Recommended Maximum Charging Current	30 A
Equalization and Cycle Service	14.6 to 14.8 VDC/unit Average at 25°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for more than 6 months at 25°C. Self-discharge ratio less than 3% per month at 25°C. Please charge batteries before using.
Terminal	Terminal F9
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.

Dimensions

Unit: mm Dimension: 410(L)×109(W)×293(H)



Terminal F9



Constant Current Discharge Characteristics: A (25°C)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
9.60V	302.2	231.6	172.4	100.5	62.42	38.54	26.19	21.12	17.53	15.47	11.55	10.72	5.67
10.0V	293.4	220.3	168.9	99.2	61.59	37.76	25.70	20.82	17.37	15.33	11.50	10.61	5.57
10.2V	284.7	212.5	165.3	97.7	61.00	37.36	25.48	20.61	17.26	15.23	11.40	10.51	5.46
10.5V	255.7	196.1	157.4	95.0	60.25	36.87	25.25	20.30	17.12	15.10	11.29	10.40	5.36
10.8V	230.8	178.8	145.1	91.8	59.42	36.57	24.95	19.61	17.03	15.03	11.25	10.31	5.30
11.1V	198.0	159.8	130.2	88.3	58.01	35.10	24.47	19.33	16.91	14.92	11.16	10.19	5.09

Constant Power Discharge Characteristics: W (25°C)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
9.6V	3188	2466	1873	1150	723.3	451.6	308.3	252.8	210.0	185.3	138.3	126.0	67.02
10.0V	3125	2390	1847	1138	716.7	446.1	303.7	249.2	208.1	183.6	137.7	125.0	65.86
10.2V	3068	2327	1826	1128	712.5	442.9	302.4	246.9	206.9	182.5	136.7	123.9	64.64
10.5V	2793	2167	1744	1105	707.9	437.3	299.9	243.5	205.2	181.1	135.5	122.7	63.42
10.8V	2552	1988	1627	1079	698.8	434.1	296.6	235.3	204.3	180.2	134.9	121.5	62.81
11.1V	2214	1803	1482	1049	688.4	417.8	291.6	231.9	203.5	179.6	134.0	120.2	60.56

All mentioned values are average values (Tolerance ±2%).

Effect of temperature on long term float life



Storage characteristic




Supplementary charge required (Carry out supplementary charge before use if 100% capacity is required)

Supplementary charge required before use. This supplementary charge will help to recover the capacity and should be made as early as possible.


Supplementary charge may often fail to recover the capacity. The battery should never be left standing till this state is reached

Supplementary charge and storage guidelines

Charge characteristic Curve for standby use



Discharge characteristic Curve



Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	6V&12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%
	2V	60%	75%	85%	88%	92%	99%	100%	103%	105%	106%
AGM Battery	6V&12V	46%	66%	76%	83%	90%	98%	100%	103%	107%	109%
	2V	55%	70%	80%	85%	92%	99%	100%	104%	108%	110%

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/cell	1.75V	1.70V	1.60V
Discharge Current (A)	(A) ≤ 0.2C	0.2C < (A) < 1.0C	(A) ≥ 1.0C

Charge the batteries at least once every six months, if they are stored at 25°C.

Charging Method:

Constant Voltage	-0.2Cx2h+14.4-14.7Vx24h, Max. Current 0.3C
Constant Current	-0.2Cx2h+0.1Cx12h
Fast	-0.2Cx2h+0.3Cx4h

Bolt	M5	M6	M8
Terminal	F3 F4 F13 F18 T25 T26	F8 F11 F12-1 F15	F5 F9 F10 F12 F14 F16
Torque	6~7N-m	8~10N-m	10~12N-m

Maintenance & Cautions

Float Service:

※ Every month, recommend inspection every battery voltage.

※ Every three months, recommend equalization charge for one time.

Equalization charge method:

Discharge: 100% rate capacity discharge.

Charge: Max. current 0.3CA, constant voltage 14.4-14.7V charge 24h.

※ Effect of temperature on float charge voltage: -3mV/°C/Cell.

※ Length of service life will be directly affected by the number of discharge cycles, depth of discharge, ambient temperature and charging voltage.