

PRODUCT INFORMATION

Product code	60533
Product code (long)	IE-DL-DLR300x-36-2700-4000K
Product description	Flat panel 301mm X 301mm
EAN code	5999097605333
Category	Downlight

PHOTOMETRIC DATA

Nominal luminous flux	2800 Lm
Rated luminous flux	2800 Lm
Nominal beam angle (half-peak value)	120 °
Rated beam angle (half-peak value)	120 °
Correlated colour temperature	4000K
Colour temperature designation	Neutral white
Colour rendering index (Ra)	80 Ra
Colour consistency	6 SDCM

LIFE SPAN

Nominal life time	30000 h
Rated life time	30000 h
Number of switching cycles	15000
Lumen main.fact.at end of nom.life time	0,7

ELECTRICAL DATA

Nominal wattage	36 W
Rated wattage	36,0 W
Nominal voltage	220-240V
Operating frequency	50/60 Hz
Nominal current	700 mA
Power factor	0.9

MECHANICAL DATA

Overall length	301 mm
Overall width	301 mm
Overall height	21 mm
Lamp shape	Square
Weight	1,110 kg
Mounting	Recessed

ADDITIONAL TECHNICAL INFORMATION

Starting time	1,0 s
Optimum operating ambient temperature	25°C
Lamp finish	Milky cover
Dimming	non-dimmable
Energy efficiency class	A+
Energy consumption	36,0 kWh/100h
Electrical protection class	CLASS II
IP rating	IP20

