

## PRODUCT INFORMATION

|                     |                             |
|---------------------|-----------------------------|
| Product code        | 60629                       |
| Product code (long) | IE-E14-5-470-6500K-160-C-G3 |
| Product description | E14 5W 160° LED Candle      |
| EAN code            | 5999097606293               |
| Category            | Retrofit                    |

## PHOTOMETRIC DATA

|                                      |          |
|--------------------------------------|----------|
| Nominal luminous flux                | 470 Lm   |
| Rated luminous flux                  | 470 Lm   |
| Nominal beam angle (half-peak value) | 160 °    |
| Rated beam angle (half-peak value)   | 160 °    |
| Correlated colour temperature        | 6500K    |
| Colour temperature designation       | Daylight |
| Colour rendering index (Ra)          | 80 Ra    |
| Colour consistency                   | 6 SDCM   |

## LIFE SPAN

|                            |         |
|----------------------------|---------|
| Nominal life time          | 15000 h |
| Rated life time            | 15000 h |
| Number of switching cycles | >7500   |

## ELECTRICAL DATA

|                                     |          |
|-------------------------------------|----------|
| Nominal wattage                     | 5 W      |
| Rated wattage                       | 5,0 W    |
| Nominal voltage                     | 220-240V |
| Operating frequency                 | 50/60 Hz |
| Nominal current                     | 43 mA    |
| Power factor                        | 0.5      |
| Wattage of equivalent filament lamp | 40W      |

## MECHANICAL DATA

|                  |          |
|------------------|----------|
| Overall diameter | 37 mm    |
| Overall height   | 103 mm   |
| Lamp shape       | Candle   |
| Weight           | 0,400 kg |

## ADDITIONAL TECHNICAL INFORMATION

|                                       |                |
|---------------------------------------|----------------|
| Starting time                         | 0,5 s          |
| Optimum operating ambient temperature | 25°C           |
| Lamp cap                              | E14            |
| Lamp finish                           | milky PC cover |
| Dimming                               | non-dimmable   |
| Energy efficiency class               | A+             |
| Energy consumption                    | 5,0 kWh/100h   |

