

Yuasa Technical Data Sheet

Yuasa DCB605-6(DT) Pro-Spec Deep Cycle Battery



Specifications

| | |
|------------------------------|-----|
| 5-hr rate Capacity to 10.5V | 175 |
| at 20°C (Ah) | |
| 20-hr rate Capacity to 10.5V | 210 |
| at 20°C (Ah) | |
| Capacity @ 75A (mins) | 105 |
| Capacity @ 25A (mins) | 383 |

5-Hr Capacity By Temperature

| | |
|------|------|
| 40°C | 105% |
| 30°C | 100% |
| 0°C | 80% |

Dimensions

| | |
|----------------------------|-----|
| Length (mm) | 259 |
| Width (mm) | 179 |
| Height (mm) | 245 |
| Height over terminals (mm) | 273 |
| Mass (kg) | 27 |

Material Specifications

| | |
|----------------------------|------------------------------------|
| Cover Style | : Removable - Maintenance Possible |
| Cover Vent Style | : Gang style |
| Container & Cover Material | : Black polypropylene plastic |
| Case to Cover Seal Method | : Heat sealing |
| Inner Cell Connector Type | : Through-partition weld |
| Plate Lug Weld Method | : Automated cast-on process |
| Positive Grid Material | : Antimony lead alloy |
| Negative Grid Material | : Antimony lead alloy |

