

Classic OPzS blocks / 12V 3 OPzS 150 LA D

INDUSTRIAL BATTERIES / NETWORK POWER

Classic OPzS batteries have been proven energy suppliers for decades, which convince in robustness, reliability and extremely long design- or cycle life.

Part Number: NVZS120150DC0FB

APPLICATIONS



SPECIFICATIONS

- Very high operational reliability under rough operating conditions
- Low maintenance due to optimised alloy and large electrolyte reserve
- 20 years design life at 20 °C ambient temperature (80 % remaining capacity from C₁₀)
- Container made from high quality translucent plastics
- Also available in dry charged condition with separate electrolyte
- Low gassing acc. to EN 50272-2 thanks to the low antimony alloy (< 3%)
- Designed in accordance with IEC 60896-11, DIN 40736 and DIN 40737 T3
- Electrolyte: diluted sulphuric acid dN = 1.24 kg/l
- Manufactured in Europe in our ISO 9001 certified production plants



Design life
20 years



Block battery



Tubular plate



Recyclable



Low
maintenance

RECYCLE WITH EXIDE.



Exide Technologies takes pride in its commitment to a better environment. An integrated approach to manufacturing, distributing and recycling of lead-acid batteries has been developed to ensure a safe and responsible life cycle for all of its products.



For more information please
[contact your local dealer](#)

TECHNICAL CHARACTERISTICS AND DATA


Nominal voltage	12 V
Float charge	2,23 V/C @ 20 °C
Capacity	CC 10h 1,8V/C 20°C 150Ah
Short circuit current	1884 A (IEC60896-21/22)
Internal resistance	6,46 mΩ (IEC60896-21/22)
Electrolyte density	1,24 kg/l

Terminal	F-M8
Terminal Torque	12 Nm
Container	PP (Polypropylene)
Temperature range	-20°C to 55°C
Dimensions (l x b/w x h)	380 x 206 x 347 mm
Weight	45 kg
Acid weight	19 kg
Origin	La Cartuja, Spain

CONSTANT CURRENT DISCHARGE

A @ 20 °C	5 min	10 min	15 min	30 min	1 h	2 h	3 h	4 h	5 h	6 h	8 h	10 h
1,900 V/C	99	84	76	64	47,2	34,1	26,4	22,3	19,7	17,7	14,6	12
1,870 V/C	120	102	90	75	55	39,5	30	25,4	22	19,8	16,4	13,8
1,850 V/C	130	112	103	81	59,8	42	31,5	27,1	23	20,7	17,1	14,2
1,830 V/C	140	122	115	87	64,6	44,4	33,4	28,3	24,1	21,6	17,9	14,6
1,800 V/C	160	135	120	95	70,4	47,1	36	29,8	25,7	22,7	18,6	15
1,750 V/C	185	155	136	102	73,4	50	38,4	31,2	27	24	19,4	15,3
1,700 V/C	210	174	155	115	79,3	52	38,6	32	28,2	24,8	19,9	15,6
1,670 V/C	229	186	163	118	82	52,6	39	32,2	28,5	25,2	20,1	15,7
1,650 V/C	240	193	168	120	83	53	39,2	32,4	28,6	25,5	20,2	15,7

Technical drawing



Float Voltage vs Temperature

