

PRODUCT INFORMATION

| | |
|---------------------|-----------------------------|
| Product code | 60624 |
| Product code (long) | IE-E14-4-320-3000K-160-C-G3 |
| Product description | E14 4W 160° LED Candle |
| EAN code | 5999097606248 |
| Category | Retrofit |

PHOTOMETRIC DATA

| | |
|--------------------------------------|------------|
| Nominal luminous flux | 320 Lm |
| Rated luminous flux | 320 Lm |
| Nominal beam angle (half-peak value) | 160 ° |
| Rated beam angle (half-peak value) | 160 ° |
| Correlated colour temperature | 3000K |
| Colour temperature designation | Warm white |
| Colour rendering index (Ra) | 80 Ra |
| Colour consistency | 6 SDCM |

LIFE SPAN

| | |
|----------------------------|---------|
| Nominal life time | 15000 h |
| Rated life time | 15000 h |
| Number of switching cycles | >7500 |

ELECTRICAL DATA

| | |
|-------------------------------------|----------|
| Nominal wattage | 4 W |
| Rated wattage | 4,0 W |
| Nominal voltage | 220-240V |
| Operating frequency | 50/60 Hz |
| Nominal current | 37 mA |
| Power factor | 0.4 |
| Wattage of equivalent filament lamp | 30W |

MECHANICAL DATA

| | |
|------------------|----------|
| Overall diameter | 37 mm |
| Overall height | 103 mm |
| Lamp shape | Candle |
| Weight | 0,030 kg |

ADDITIONAL TECHNICAL INFORMATION

| | |
|---------------------------------------|----------------|
| Starting time | 0,5 s |
| Optimum operating ambient temperature | 25°C |
| Lamp cap | E14 |
| Lamp finish | milky PC cover |
| Dimming | non-dimmable |
| Energy efficiency class | A+ |
| Energy consumption | 4,0 kWh/100h |

