

SOLIDLINE

Designed by Ledlenser

PRODUCT DATA SHEET

Solidline SAL2R



Solidline SAL2R

PRODUCT DESCRIPTION

Impressively bright, impressively versatile: The Solidline SAL2R is a compact LED area light with a powerful performance package for many fields of use around the house, garden and workshop. Whether by stand, tripod thread, carabiner or magnet – this work light can be positioned extremely flexibly. From any position, the SAL2R shines with its large function package and offers white light in four different color temperatures with four brightness levels each. Combining this with the available red light in constant or flashing mode it offers an impressive 18 different light functions. The robust powerhouse is fuelled by a powerful, integrated rechargeable battery that can also be used as a power bank.

- Compact, powerful LED spotlight with 18 different light functions and a power bank function (USB-A output)
- Four available white light color temperatures (2700-6500K) with four brightness levels each; additional red light function (constant or flashing)
- 180° swiveling lamp head for flexible alignment of the light beam
- Base magnet, integrated snap hook and tripod thread for flexible mounting
- Easily rechargeable via USB-C; integrated battery and charge level indicator

TECHNICAL DATA

Width [mm]	98
Depth [mm]	45
Height [mm]	111
Weight incl. batteries [g]	465
Focus function	No
Primary material	ABS
Secondary material	Other plastics
Cartridge	No

POWER SUPPLY

Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery replaceable	No
Total battery voltage [V]	3.7
Total battery capacity [mAh]	13500
Total battery energy ² [Wh]	49.5
Rechargeable	Yes
Charging time ⁵ [min]	360
Energy modes	Energy Saving
Energy status indicator	Battery Indicator, Charge Indicator, Low Battery Warning

FURTHER SPECIFICATIONS

IP class	IP54
Drop test (drop height) [m]	1
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Low Power, Mid Power, Power, Boost

LIGHT SOURCE

Amount LEDs	1
LED type	COB LED
Color	White
Color temperature [K]	2700 to 6500
Color rendering index (CRI)	70

LEDLENSER VALUES

Energy Saving	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]	1500	750	300	120
Beam distance ¹ [m]	60	40	25	10
Run time ¹ [h]	6	10	25	65

SWITCH

End Cap Switch, Multifunctional Switch

FEATURES

Red Light

TECHNOLOGIES

Power Bank Function

Solidline SAL2R

PACKAGING AND LOGISTICS



PACKAGING INFORMATION

Type of packaging	Blister
Scope of delivery	USB cable
Item No.	502742
Customs tariff number	8513100000
Color	black

SINGLE PACKAGE

Dimensions W x H x D [cm]	15 x 28 x 7.2
Gross weight [g]	600
GTIN-13	4058205030694

INNER CARTON

Unit	6
Dimensions W x D x H [cm]	38 x 28.7 x 32.5
Gross weight [g]	4180
GTIN-13	4058205030687

EXPORT CARTON

Unit	12
Dimensions W x D x H [cm]	61.5 x 41 x 36.5
Gross weight [kg]	9.36
GTIN-13	4058205030670

Solidline SAL2R

PRODUCT SERIES

The Solidline

High quality, low prices

Best quality for budget-conscious users of portable light – this is the concept behind the Solidline range designed and engineered by Ledlenser. The Solidline headlamps, flashlights, area lights, worklights, lanterns and multi-purpose lights offer outstanding technologies and features to form a comprehensive assortment that is suitable for various purposes. In order to protect the purse even in the use phase, almost all lamps of the series are directly rechargeable versions or can also be operated with rechargeable batteries.

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode".

2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.

5) Charging time varies by hardware used.