

# SOLIDLINE

Designed by Ledlenser

## PRODUCT DATA SHEET

### Solidline SW5R



# Solidline SW5R

## PRODUCT DESCRIPTION

Whether at home, in the garage or in the workshop: the robust Solidline SW5R work light provides reliable light in many everyday situations. The wide floodlight LED illuminates rooms and surfaces evenly; it can be dimmed continuously via a rotary switch. Thanks to a separate spot LED, the SW5R can also be used as a classic flashlight with a focused beam. Magnet, ball joint and a fold-out hook in the lamp base offer flexible and individual mounting options in various work areas at any time. The integrated rechargeable battery with status indicator is quickly recharged via micro-USB.

- Versatile LED work light with two separate light sources for floodlight and focused light
- Powerful, continuously dimmable floodlight for even illumination of work areas
- Flexible mounting options thanks to integrated magnet, ball joint and fold-out hook
- Optimal handling thanks to rubberized, ergonomic handle
- Easily rechargeable via micro-USB; integrated battery and charge level indicator

### TECHNICAL DATA

Width [mm]	45
Depth [mm]	40
Height [mm]	384
Weight incl. batteries [g]	260
Focus function	No
Primary material	Other plastics
Secondary material	Other plastics
Cartridge	No

### POWER SUPPLY

Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery replaceable	No
Total battery voltage [V]	3.7
Total battery capacity [mAh]	2600
Total battery energy <sup>2</sup> [Wh]	9.62
Rechargeable	Yes
Charging time <sup>5</sup> [min]	240
Energy modes	Constant Light
Energy status indicator	Battery Indicator, Charge Indicator, Low Battery Warning

### FURTHER SPECIFICATIONS

IP class	IP54
Drop test (drop height) [m]	2
IK Code [J]	7
Working temperature range [°C]	-10 to +40

### LIGHT FUNCTIONS

Low Power, Power

### LIGHT SOURCE

	COB	Alternate
Amount LEDs	1	1
LED type	COB LED	Power LED
Color	White	White
Color temperature [K]	6000 to 7000	5500 to 6500
Color rendering index (CRI)	80	70

### LIGHT VALUES - COB

Constant Light	Boost	Power	Mid Power	Low Power
Light output <sup>1</sup> [lm]		800		70
Beam distance <sup>1</sup> [m]		40		10
Run time <sup>1</sup> [h]		2		18

### LIGHT VALUES - Alternate

Constant Light	Boost	Power	Mid Power	Low Power
Light output <sup>1</sup> [lm]		130		
Beam distance <sup>1</sup> [m]		25		
Run time <sup>1</sup> [h]		12		

### SWITCH

Rotary Switch, Front Switch

### FEATURES

Stepless dimming

# Solidline SW5R

## PACKAGING AND LOGISTICS



Exemplary package illustration

### PACKAGING INFORMATION

Type of packaging	Blister
Scope of delivery	USB cable
Item No.	502893
Customs tariff number	8513100000
Color	black

### SINGLE PACKAGE

Dimensions W x H x D [cm]	11 x 42 x 4.5
Gross weight [g]	396
GTIN-13	4058205032797

### INNER CARTON

Unit	6
Dimensions W x D x H [cm]	42.7 x 30.5 x 12
Gross weight [g]	2662
GTIN-13	4058205032780

### EXPORT CARTON

Unit	24
Dimensions W x D x H [cm]	45.5 x 33.5 x 53
Gross weight [kg]	11.5
GTIN-13	4058205032773

# Solidline SW5R

## The Solid Line

### High quality, low prices

Best quality for budget-conscious users of portable light – this is the concept behind the Solidline range designed and engineered by Ledlenser. The Solidline headlamps, flashlights, area lights, worklights, lanterns and multi-purpose lights offer outstanding technologies and features to form a comprehensive assortment that is suitable for various purposes. In order to protect the purse even in the use phase, almost all lamps of the series are directly rechargeable versions or can also be operated with rechargeable batteries.

---

## FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode".

2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.

5) Charging time varies by hardware used.